



## Specifications

	Channel 1	Channel 2	Channel 3	Channel 4	DC1	DC2
Heatshrink Color	Black	Red	Yellow	Blue	Orange	Brown
Interface	SMA (50 ohms)	SMA (50 ohms)	SMA (50 ohms)	SMA (50 ohms)	SMA	
Style	L Type	L Type	L Type	L Type	L Type	
Frequency Range	DC to 2.2 GHz	DC to 2.2 GHz	DC to 2.2 GHz	DC to 2.2 GHz	DC	
Peak Power, Max.	500 W	500 W	500 W	500 W		
Average Power	5 W	5 W	5 W	5 W		
VSWR, Max.	2.00	2.00	2.00	2.00		
VSWR WOW (360° Max.)	0.25	0.25	0.25	0.25		
Insertion Loss, Max.	1.5 dB (2.5 dB max)	1.5 dB (2.5 dB max)	1.5 dB (2.5 dB max)	1.5 dB (2.5 dB max)		
Insertion Loss WOW, Max.	0.25 dB	0.25 dB	0.25 dB	0.25 dB		
Isolation	40 dB (30 dB typ min)					
Current Capacity	1.0 AMP					3.0 AMP
Voltage	0- 48 VDC					0- 48 VDC
Rotation Speed, Max.	60 rpm					
Life, Min.	2 Million Revolutions					